30 inch Built-In Bottom Mount

Master Series



REF30PIXR

Bertazzoni built-in refrigerators are designed, engineered and made in Italy with the highest grade materials and components. The proprietary 'lift & swing' door hinge system makes them the ideal choice for true flush installation as a single unit or sideby-side. Using one of the available handle kits in Professional, Master and Heritage Series style, these refrigerators integrate seamlessly with all other Bertazzoni appliances into style-harmonized suites for a true, high-performing kitchen.

These built-in refrigerators are built to last forever, employing metal and glass inside and out for better temperature management. The lateral airflow system, with dual compressor and evaporator for refrigerator and freezer, reduces cold air los when opening doors and allows for category-leading interior depth. The internal configuration is designed for maximum flexibility, with 11 cubic feet of refrigerator volume and 3 cubic feet of FlexMode volume. The FlexMode Refrigerator-Freezer allows to switch the bottom compartment between freezer and refrigerator with one touch. Interior LED lighting on top and sid provide bright interior illumination on all levels with minimal energy consumption. Integrated water filter connected to water lin ensures regular production of ice cubes of customizable size. Replacement water filters are available for purchase here

All Bertazzoni appliances are covered by a 2-year warranty. Products and packaging are 99% recyclable. [6]

Specifications

Features Refrigerator Size 30 in Style bottom mount Finishing stainless steel User interface digital display inside Lighting 6 LED lights recessed into refrigerator ceiling, 5 side wall flush mounted individual Shelves 2 Door storage 3 full-width racks Handle style Professional Series Ice maker yes Drawer refrigerator 2 2 Drawers FlexMode Modes Max Cool Fridge, Vacation, Beverage Cooler, SuperIce, IceSize, Sabbath Mode, Wate Filter DOE compliant yes Refrigerator capacity 11.00 cu.ft³ FlexMode capacity 2.9 cu.ft³ Certification ETL **Technical specifications** Electrical supply 115 V - 60 Hz - 4.8 A

Dimensions

